

Fiberglass Tanks

NOV® fiberglass storage tanks are manufactured by a skilled group of operators and technicians, using the standards that are set forth in ASTM 3299, ASTM 4097, ASME RTP1, and API 12P.

NOV's ability to deliver on time is unsurpassed in the tank manufacturing industry. NOV fiberglass tanks are manufactured in various sizes and types to meet the customers' needs. Fiberglass tanks should be used to temporarily hold fresh or salt water.

Isophalic and vinyl ester resins are available upon request, either as a liner for a normal fiberglass tank or with the tank being built 100% of specialized resins.

All tanks can be built to most specs requested by the customer and can have any combination of Victaulic, flanged, or threaded connections.

Gun barrels can also be built to these sizes:

- 400 bbl
- 500 bbl
- 750 bbl
- 1000 bbl



Fiberglass Tank



Fiberglass Tanks

Sizes Available

Capacity (bbl)	Diameter	Height
210	10'	15'
210	15' 6"	6' 4"
300	12'	15'
300	15' 6"	9'
400	12'	20'
400	15' 6"	12'
500	12'	25'
500	15' 6"	16'
750	15' 6"	24'
1000	15' 6"	30'

Steel Tanks

NOV manufactures API 12F monogrammed and non-monogrammed steel tanks. Both are built to API specs and are built in San Angelo, Texas. NOV steel tanks are primarily used to temporarily store oil and saltwater at customer lease sites. Steel tanks are provided in the standard sizes in the table below.

Gun barrels available:

- 300 bbl
- 400 bbl
- 500 bbl
- 750 bbl
- 1000 bbl

All steel tanks are sub-arc'ed and internal coating is available upon request.

NOV also manufactures stairways, walkways, and other customized products to be used with its tanks at lease sites.



Steel Tank



Stairways and Walkways

Sizes Available

Capacity (bbl)	Diameter	Height
210	12'	10' 6"
210	10'	15'
210	15' 6"	6' 4"
300	12'	15'
300	15' 6"	9'
400	12'	20'
400	15' 6"	12'
400	14'	16'
500	12'	25'
500	13' 6"	20'
500	15' 6"	16'
750	15' 6"	24'
1000	15' 6"	30'